



THE MOST RELIABLE WELDING®

HOFFMAN ARC CO., LTD

QUALITY CERTIFICATE OF WELDING CONSUMABLE

Type	Norm	Brand Name	Part #	Diameter	Lot No.	Manufactured Date	Date of Issue
AWS E7018	AWS A5.1/A5.1M ASME SFA-5.1/SFA-5.1M	SINNVOLL	6001803	5/32" (4.0mm)	26-81006	SHOWN ON PACKAGE	26 / 02 / 2026

Mechanical Properties of Deposited Metal	Chemical Composition of Deposited Metal [%]
--	---

Item		Requirement	Actual Result	Element	Requirement	Actual Result	Element	Requirement	Actual Result	
Yield Strength Rel(MPa)		≥400	448	C	≤0.15	0.09	Mo	≤0.30	0.004	
Tensile Strength Rm(MPa)		≥490	554	Si	≤0.75	0.45	V	≤0.08	0.003	
Elongation A[%]		≥22	26	Mn	≤1.60	1.15	Cu	--	--	
Impact Test	Impact Temp (°C)	-30	-30	S	≤0.035	0.015	Ti	--	--	
	Impact Absorbed Energy (J)	≥27	106 113 104	P	≤0.035	0.022	Al	--	--	
X-Ray		Required	Complies	Cr	≤0.20	0.03	--	--	--	
Hydrogen Content (ml/100g)		--	--	Ni	≤0.30	0.01	Fillet weld test of T-joint		--	
Approved Classification Grade		CCS (--)	LR (--)	GL (--)	NK (--)	ABS (--)	BV (--)	DNV (--)	KR (--)	RINA (--)

10050 NW 116TH Way, Suite 15.
Medley, Florida 33178.
Telf: 305-4205099

This is to certify that the welding consumable conform with the standard

Signature

Inspection seal

