



THE MOST RELIABLE WELDING®

HOFFMAN ARC CO., LTD

QUALITY CERTIFICATE OF WELDING CONSUMABLE

Type	Norm	Brand Name	Part #	Diameter	Lot No.	Manufactured Date	Date of Issue
AWS E7018	AWS A5.1/A5.1M ASME SFA-5.1/SFA-5.1M	SINNVOLL	6001802	1/8" (3.2MM)	25-81038	SHOWN ON PACKAGE	03 / 04 / 2025

Mechanical Properties of Deposited Metal			Chemical Composition of Deposited Metal (%)						
Item		Requirement	Actual Result	Element	Requirement	Actual Result	Element	Requirement	Actual Result
Tensile Strength Rel(MPa)		≥490	554	C	≤0.1500	0.06	Mo	≤0.3000	0.002
Yield Strength Rm(MPa)		≥400	448	Si	≤0.75	0.46	V	≤0.0800	0.007
Elongation A5 (%)		≥22	25.5	Mn	≤1.6000	1.12	Cu	--	--
Impact Test	Impact Temp (°C)	-30	-30	S	≤0.0350	0.01	Ti	--	--
	Impact Absorbed Energy (J)	≥27	113 107 102	P	≤0.0350	0.019	Al	--	--
X-Ray		--	Complies	Cr	≤0.2000	0.03	--	--	--
Limit of Moisture Content, % by Wt, Max.		--	--	Ni	≤0.3000	0.01	Fillet weld test of T-joint		Complies
Approved Classification Grade		CCS (--)	LR (--)	GL (--)	NK (--)	ABS (--)	BV (--)	DNV (--)	KR (--) RINA (--)
10050 NW 116TH Way, Suite 15. Medley, Florida 33178. Telf: 305-4205099				This is to certify that the welding consumable conform with the standard Signature APPROVED BY LIAO YUGANG Inspection seal HoffmanArc					